
Ribbon dimensions and effective cross-sectional area

TOKYO RESISTANCE WIRE CO., LTD.

1-8-29 Kamata Ohta-Ku, Tokyo 144-0052

Phone : +81-3-3736-5201

Faxmile : +81-3-3736-5429

mail : mail@tokyo-resistance-wire.com

http : [//main.tokyo-resistance-wire.com](http://main.tokyo-resistance-wire.com)

Ribbon dimensions and effective cross-sectional area

Thickness (m)	Width (mm)														
	40	32	25	20	16	13	10	6.5	5.0	3.2	2.4	1.6	0.8	0.4	
2.90	113.7	90.94	71.05	56.84	45.47	36.95	28.42								
2.60	101.9	81.54	63.70	50.96	40.77	33.12	25.48	16.22							
2.30	90.16	72.13	56.35	45.08	36.06	29.30	22.54	14.35	11.04						
2.00	78.40	62.72	49.00	39.20	31.36	25.48	19.60	12.48	9.600						
1.80	70.56	56.45	44.10	35.28	28.22	22.93	17.64	11.23	8.640						
1.60	62.72	50.18	39.20	31.36	25.09	20.38	15.68	9.984	7.680						
1.40	54.88	43.90	34.30	27.44	21.95	17.84	13.72	8.736	6.720						
1.20	47.04	37.63	29.40	23.52	18.82	15.29	11.76	7.488	5.760						
1.00	39.20	31.36	24.50	19.60	15.68	12.74	9.800	6.240	4.800						
0.90		28.22	22.05	17.64	14.11	11.47	8.820	5.616	4.320	2.765	2.074				
0.80		25.09	19.60	15.68	12.54	10.19	7.840	4.992	3.840	2.458	1.843				
0.70			17.15	13.72	10.98	8.918	6.860	4.368	3.360	2.150	1.613				
0.60			14.70	11.76	9.408	7.644	5.880	3.744	2.880	1.843	1.382				
0.50			12.25	9.800	7.840	6.370	4.900	3.120	2.400	1.536	1.152				
0.45			11.03	8.820	7.056	5.733	4.410	2.808	2.160	1.382	1.037	0.69120			
0.40					6.272	5.096	3.920	2.496	1.920	1.229	0.9216	0.61440			
0.35						4.459	3.430	2.184	1.680	1.075	0.8064	0.53760			
0.32						4.077	3.136	1.997	1.536	0.9830	0.7373	0.49150			
0.29							2.842	1.810	1.392	0.8909	0.6682	0.44540	0.2227		
0.26							2.548	1.622	1.248	0.7987	0.5990	0.39940	0.1997	0.09984	
0.23								1.435	1.104	0.7066	0.5299	0.35330	0.1766	0.02204	
0.20								1.248	0.9600	0.6144	0.4608	0.30720	0.1536	0.07680	
0.18								1.123	0.8640	0.5530	0.4147	0.27650	0.1382	0.06912	
0.16										0.4915	0.3686	0.24580	0.1229	0.06144	
0.14										0.4301	0.3226	0.21500	0.1075	0.05376	
0.12											0.2765	0.18430	0.09216	0.04608	
0.10												0.15360	0.07680	0.03840	
0.08													0.12290	0.06144	0.03072