
Insulating Coatings

(Glass , Silk rolling) Dimensions

Insulating Coatings
SG.DG.SS.DS Processing is currently suspended.

TOKYO RESISTANCE WIRE CO., LTD.

1-8-29 Kamata Ohta-Ku, Tokyo 144-0052

Phone : +81-3-3736-5201

Faxmile : +81-3-3736-5429

mail : mail@tokyo-resistance-wire.com

http : [//main.tokyo-resistance-wire.com](http://main.tokyo-resistance-wire.com)

Insulating Coatings

(Glass , Silk rolling) Dimensions

Insulating Coatings
SG.DG.SS.DS Processing is currently suspended.

Diameter (mm)	SG(Single glass rolling) Maximum temperature 180°C		DG(Double glass rolling) Maximum temperature 180°C		SS(Single glassrolling) Maximum temperature 105°C		DS(Double glass rolling) Maximum temperature 105°C	
	Heat resistance differentiation A		Heat resistance differentiation A		Heat resistance differentiation H		Heat resistance differentiation H	
	Minimum thickness (mm)	Maximum outside diameter (mm)	Minimum thickness (mm)	Maximum outside diameter (mm)	Minimum thickness (mm)	Maximum outside diameter (mm)	Minimum thickness (mm)	Maximum outside diameter (mm)
1.20			0.10	1.49				
1.00	0.06	1.170	0.10	1.29	0.030	1.08	0.050	1.160
0.90	0.06	1.060	0.10	1.18	0.025	0.960	0.040	1.040
0.85	0.06	1.010	0.10	1.13	0.025	0.940	0.040	0.970
0.80	0.06	0.960	0.10	1.08	0.025	0.860	0.040	0.940
0.75	0.06	0.910	0.10	1.03	0.025	0.840	0.040	0.870
0.70	0.06	0.860	0.10	0.980	0.025	0.760	0.040	0.840
0.65	0.06	0.810	0.10	0.920	0.025	0.710	0.040	0.780
0.60	0.06	0.760	0.10	0.880	0.020	0.670	0.040	0.710
0.55	0.06	0.710	0.10	0.830	0.020	0.620	0.040	0.660
0.50	0.06	0.650	0.10	0.750	0.020	0.570	0.040	0.610
0.45	0.06	0.600	0.10	0.700	0.020	0.520	0.040	0.560
0.40	0.06	0.550	0.10	0.650	0.020	0.465	0.040	0.510
0.35	0.06	0.500	0.10	0.600	0.020	0.415	0.035	0.453
0.32	0.06	0.470	0.10	0.570	0.020	0.380	0.035	0.415
0.29	0.06	0.440	0.10	0.540	0.020	0.350	0.035	0.385
0.26	0.06	0.410	0.10	0.510	0.020	0.320	0.035	0.353
0.23	0.06	0.378	0.10	0.478	0.020	0.290	0.035	0.323
0.20	0.06	0.348	0.10	0.448	0.020	0.258	0.035	0.298
0.18	0.06	0.328	0.10	0.428	0.015	0.223	0.030	0.267
0.16	0.06	0.308	0.10	0.408	0.015	0.213	0.030	0.246
0.15	0.06	0.298	0.10	0.398	0.015	0.201	0.030	0.236
0.14	0.06	0.288	0.10	0.388	0.015	0.191	0.030	0.226
0.12			0.06	0.300	0.015	0.171	0.030	0.205
0.10			0.06	0.270	0.015	0.150	0.025	0.181
0.09			0.06	0.260	0.015	0.140	0.025	0.171
0.08			0.06	0.250	0.015	0.129	0.025	0.162
0.07			0.06	0.240				
0.06			0.06	0.230				