
Spool Specifications

TOKYO RESISTANCE WIRE CO., LTD.

1-8-29 Kamata Ohta-Ku, Tokyo 144-0052

Phone : +81-3-3736-5201

Faxmile : +81-3-3736-5429

mail : mail@tokyo-resistance-wire.com

http : [//main.tokyo-resistance-wire.com](http://main.tokyo-resistance-wire.com)

Spool Specifications

Code	diameter [D] [mm]	diameter [d] [mm]	Width [W] [mm]	Hole diameter [h] [mm]	diameter [a] [mm]	Total length [L] [mm]	Weight [g]
P-2G	60	30	50	15	5	60	30
P-3G	70	35	50	15	5	60	50
P-5G	80	40	70	15	6	82	85
P-1	100	50	70	16	10	90	105
P-3	130	60	90	20	10	110	170
P-5	160	70	90	20	12	114	300
P-10	200	90	110	25	12	134	500
P-15	250	110	110	30	15	140	890
P-30	300	130	130	30	15	160	1300
P-3R	130	80	90	20	10	110	250
P-5R	160	90	90	20	12	114	390
DIN80	80	50	64	16	8	80	70
DIN100	100	63	80	16	10	100	125
NS-5	120	54	130	15	10	150	195
HK76/16-60	63	44	51	16	4	60	50

